

# **ROMBICUS®**

Rectangular, double-walled, storage container for the storage of water-endangering liquids, authorised by DIBt with the Certification No. Z-38.12-259 for the indoor and outdoor installation.

Also for use as storage or collection containers for old goods, on request with feed hopper.

Implementation in steel/steel, stainless steel/steel, or complete in stainless steel.



**COMPACT**

**SECURE**

**ROBUST**

**SPACE-SAVING**

**ERGONOMIC**

## **Container basic equipment:**

- **Double-walled steel design**
- **Energy-independent vacuum leakage monitoring**
- **Optical content display dial**
- **Various reserve couplings**
- **With DN 100 flange**
- **Filling, suction and venting line**
- **Limit indicator switch**
- **With collection trough for drop leakage**
- **Prepared for attachment/fixing of a pump bracket or a double wing door cabinet**
- **On request, closed drive-under pallet**
- **Lifting lug**
- **Manhole approx. 400 x 500 mm**

# **ROMBICUS®**

## Technical data

<b>ROMBICUS Type</b>	<b>400</b>	<b>700</b>	<b>1000</b>	<b>1300</b>	<b>1600</b>	<b>2000</b>	<b>2400</b>	<b>3000</b>	<b>5000</b>
Volume gross approx. litre	400	700	1000	1300	1600	2000	2400	3000	5000
Volume 95% approx. litre	380	665	950	1235	1520	1900	2280	2850	4750
Length approx. mm	1192	1192	1192	1192	2192	2192	2192	2192	2392
Width approx. mm	772	772	772	772	772	772	772	1196	1396
Height* approx. mm	620	1160	1450	1700	1200	1495	1695	1480	1700
Weight** approx. kg	210	220	325	365	585	685	745	895	1230

\*With drive-under pallet

\*\*Without equipment



Illustration: with pump unit on front

### Its areas of application:

- **Operation service station**
- **Aggregate supply**
- **Employment in water-conservation areas**
- **Suitable for the installation in ocean-going container**

Rights to technical errors or changes reserved.